



TECHNICAL DATA							
MOD.	Current	Duty Cycle	Gas	Gas Pressure	Gas Flow	Pilot	Ignition
PT - 40	10-40 Amps	40 Amps 60%	Air/N2	65-75 psi (4.4-5.0 bar)	210 scfh (100 lpm)	Electrode to tip	Without HF

ITEM	Part. No	DESCRIPTION	ORIGINAL REF.	PACK
	PLTPT40.6.A	Torcia completa mt. 6 (size A) - Complete torch mt. 6 (size A)		1
	PLTPT40.6.B	Torcia completa mt. 6 (size B) - Complete torch mt. 6 (size B)		1
	PLTPT40.06	1a Corpo torcia - Torch head		1
	PLTPT246.08	1b Impugnatura - Handgrip		1
	02.09.A.BZ	1c Pulsante - Switch		1
	PLTPT246.01	2 Elettrodo - Electrode		10
	PLTPT246.01L	2a Elettrodo lungo - Extended electrode		10
	PLTR53.05	Diffusore aria - Swirl ring		10
	PLTPT246.02.06	4 Ugello 10-20 A - Tip 10-20 A		10
	PLTPT246.02.08	4 Ugello 20-30 A - Tip 20-30 A		10
	PLTPT46.02.09	4 Ugello 30-40 A - Tip 30-40 A		10
	PLTPT46.02.X09	4a Ugello taglio a croce 30-40 A - Tip 30-40 A		10
	PLTPT40.02.P09	4b Ugello piatto 30-40 A - Flat tip 30-40 A		10
	PLTPT46.02.P10	4b Ugello piatto 40-50 A - Flat tip 40-50 A		10
	PLTPT46.02.C09	Ugello taglio a contatto 30-40 A - Contact tip 30-40 A		10
	PLTPT46.02.C10	Ugello taglio a contatto 40-50 A - Contact tip 40-50 A		10
	PLTPT246.02.06L	5 Ugello lungo 10-20 A - Extended tip 10-20 A		10
	PLTPT246.02.08L	5 Ugello lungo 20-30 A - Extended tip 20-30 A		10
	PLTPT46.02.09L	5a Ugello lungo 30-40 A - Extended tip 30-40 A		10

6		PLTR30.03	Ugello esterno 6 fori	- Retaining cap 6 holes		10
		PLTPT46.03	Ugello esterno 6 fori lunga durata	- Retaining cap 6 holes maximum life		10
7		PLTPT46.03.C	Ugello esterno taglio a contatto	- Contact retaining cap		10
8		PLTPT46.04.2	Distanziale a 2 punte	- Double pointed spacer		10
9		PL_U60485	Distanziale taglio manuale	- Shield cap hand		10